

AS/NZ 3112 Plug to IEC 60320 C19 Power Cord

This power cord features an Australian AS/NZ 3112 standard plug on one end and an IEC 60320 C19 connector on the other. It is designed for connecting high-power devices to standard Australian and New Zealand power outlets.



Product Overview

High-Performance Power Connectivity

This power cord features an Australian AS/NZ 3112 standard plug on one end and an IEC 60320 C19 connector on the other, designed for reliable power delivery in commercial and industrial environments. It is engineered for high-power equipment, making it an ideal choice for servers, high-end workstations, and large network devices. With robust molded connectors and verified safety certifications, this cord ensures a secure and durable connection for critical infrastructure.

Technical Specifications

Connector Types

End	Type
Plug	Australia 3-prong (AS/NZ 3112)
Connector	IEC 60320 C19

Compatible Cable Types

- H03VV-F 3G0.5-0.75 mm²
- H05VV-F 3G0.75-2.5 mm²
- H03RT-F 3G0.75-1.0 mm²
- H05RR-F 3G0.75-1.5 mm²
- H07RN-F 3G0.75-1.0 mm²

Max Voltage	250 V
-------------	-------

Compliance & Logistics

Certifications	SAA, RoHS, REACH
Minimum Order Quantity	2000