

## AS/NZ 3112 to IEC 60320 C21 Power Cord

This power cord features an Australian AS/NZ 3112 standard plug on one end and an IEC 60320 C21 connector on the other. It is designed for connecting electrical appliances and equipment requiring a high-temperature connector to a standard Australian power outlet.



### ADDITIONAL IMAGES



### Overview

#### High-Performance Power Connectivity

This power cord is designed to connect high-power electrical appliances and equipment to standard Australian power outlets. Featuring an AS/NZ 3112 plug and an IEC 60320 C21 connector, it ensures a robust and secure connection for demanding applications. It is engineered with durable insulation and high-quality conductors to support safe, reliable power transmission in industrial and commercial environments.

### Technical Specifications

Max Voltage	250 V
Plug Type	Australia 3-prong (AS/NZ 3112)
Connector Type	IEC 60320 C21
Certifications	SAA, RoHS, REACH, CE

### Cable Options

#### Available Cable Standards

- H03VV-F 3G0.5-0.75 mm<sup>2</sup>
- H05VV-F 3G0.75-2.5 mm<sup>2</sup>
- H03RT-F 3G0.75-1.0 mm<sup>2</sup>
- H05RR-F 3G0.75-1.5 mm<sup>2</sup>
- H07RN-F 3G0.75-1.0 mm<sup>2</sup>

### Commercial Terms

Minimum Order Quantity	2000
Samples	Yes