

Automotive Dual Action Polisher

The Dual Action Polisher is a versatile tool designed for automotive detailing and paint correction. It features a variable speed control ranging from 1800 to 4800 RPM, allowing for precise adjustments based on the task.



ADDITIONAL IMAGES



Overview

Professional Automotive Dual Action Polisher

Designed for professional automotive detailing and paint correction, this dual action polisher leverages high-precision CNC manufacturing for its core transmission components. It features an integrated shaft and gear system for enhanced durability and performance. With a focus on versatility, the unit supports multiple eccentricities and pad sizes, making it an ideal choice for both small-scale detailing and comprehensive paint restoration.

Performance

Key Performance Metrics

1000 W Rated Input Power	4800 RPM Max No-load Speed	15 mm Eccentric Distance
------------------------------------	--------------------------------------	------------------------------------

Available Eccentricity

- 8
- 12
- 15
- 21

Speed Range	1800 - 4800 RPM
-------------	-----------------

Technical Specifications

Compliance & Safety

CE • EMC • SGS • RoHS

Disc Size	125 - 150 mm
Supported Voltage	110V/60Hz, 230V/50Hz

Features

Build Features

- CNC machined gearbox and polarizer
- Integrated shaft and teeth
- Imported bearings
- Fish scale antiskid rubber grip
- Multi-position D handle

Operational Functionality

- Infinitely variable speed dial
- Soft start function
- High-efficiency heat dissipation
- Replaceable brushes