

# Brass Cam and Groove Hose Fitting with PP Camlock

This brass adapter is designed for use with cam and groove hose fittings. The polypropylene cam and groove mechanism ensures secure and efficient hose connections.



## ADDITIONAL IMAGES



## Product Overview

### High-Performance Brass Camlock Coupling

This brass cam and groove hose fitting is designed for efficient, tool-free fluid transfer in industrial environments. Engineered for durability and high abrasion resistance, it provides a secure, leak-proof connection for suction or discharge hoses. It is ideal for use with pumps, tanks, and IBC containers in sectors such as the paints and inks industry.

## Technical Specifications

<b>Material</b>	Brass, Carbon Steel Plated or Stainless Steel (Pins/Rings/Clip), NBR/BUNA/EPDM/VI-TON (Seal)
<b>Available Sizes</b>	1/2 inch to 6 inches
<b>Standards</b>	A-A-59326, MIL-C-27487, DIN 2828, DIN 14420-7

## Performance Metrics

### Operating Limits

**250 psi**

Max Working Pressure

**232 °C**

Max Temperature

**-101 °C**

Min Temperature

### Important Safety Notes

- Not suitable for steam applications
- Not suitable for compressed air
- Not suitable for liquid gases

## Configuration

### Thread Options

NPT • BSPP • BSPT

### Types

A, B, C, D, E, F, DC, DP