

Brass Camlock Coupling with Viton Gaskets

This brass camlock coupling allows for quick and reliable connection of hoses and pipes. Viton gaskets provide a secure seal and compatibility with various fluids.



ADDITIONAL IMAGES



Product Overview

High-Performance Brass Camlock Couplings

These brass camlock couplings are designed for efficient, tool-free hose and pipe connections in industrial fluid transfer systems. Featuring durable brass construction and high-performance Viton gaskets, they offer excellent corrosion resistance and superior sealing capabilities. Ideal for low-pressure suction or discharge applications, these couplings provide a reliable solution for handling oils, coolants, and water in demanding environments.

Technical Specifications

Available Sizes

- 1/2"
- 3/4"
- 1"
- 1-1/4"
- 1-1/2"
- 2"
- 2-1/2"
- 3"
- 4"
- 5"
- 6"

Body Material	Brass
Gasket Material	Viton
Thread Options	NPT, BSPP, BSPT

Performance Metrics

Key Performance Metrics

250 psi

Max Working Pressure

232 °C

Max Temperature

-101 °C

Min Temperature

Compatibility & Standards

Available Coupling Types

Type A • Type B • Type C • Type D • Type E • Type F • Type DC • Type DP

Standards Compliance

A-A-59326, MIL-C-27487, DIN 2828, DIN 14420-7

Usage Guidelines

Important Usage Notes

- Not suitable for compressed air applications
- Not suitable for steam transfer
- Not suitable for liquid gases
- Ideal for oils, coolants, and water