


# Category 5e Communication Cable

This communication cable exceeds ANSI/TIA/EIA-568B.2 Category 5e standards. Its optimized outer diameter reduces twisting and tangling during installation and is suitable for horizontal subsystem connections.

► 标准：优于现行的ANSI/TIA/EIA-568B.2五类线缆标准。

► 功能及优点：传输速率低，连接稳定一致，具有优异的电磁干扰性，使传输信号的误码率明显降低。合适的外径尺寸，减少安装中的扭曲或打结。

► 产品类别：适用于水平子系统的连接。



产品编号	产品名称	包装
TXL102	超五类4对非屏蔽双绞线	305米/箱

## Product Overview

### High-Performance Category 5e Networking

This Category 5e communication cable is engineered to exceed ANSI/TIA/EIA-568B.2 standards, providing reliable performance for horizontal subsystem connections. It features low transmission delay and consistent insulation to ensure high resistance against electromagnetic interference, significantly reducing signal error rates. The optimized outer diameter is specifically designed to minimize twisting and tangling, streamlining the installation process for professionals.

## Technical Standards

### Compliance Standards

Exceeds ANSI/TIA/EIA-568B.2 • Category 5e

## Performance Metrics

### Key Performance Features

**305 m**

Length per Box

**4 Pairs**

Twisted Pairs

## Technical Specifications

### Cable Characteristics

- Low transmission delay
- Consistent insulation integrity
- High electromagnetic interference (EMI) resistance
- Reduced bit error rate (BER)
- Anti-tangle outer diameter design

## Logistics & Ordering

### Ordering Information

Product Code	Description	Packaging
TXL102	Category 5e 4-Pair Unshielded Twisted Pair (UTP)	305 Meters / Box

## Application

Recommended Application	Horizontal subsystem connections