

Ceiling-Mount Mini Array Passive Speaker, 100W RMS

This ceiling-mount mini array passive speaker is engineered for high-quality audio reproduction. Its modular design allows for flexible configuration, making it suitable for different room sizes and acoustic requirements.



ADDITIONAL IMAGES



Overview

Professional Ceiling-Mount Mini Array

This ceiling-mount mini array passive speaker is engineered for high-quality audio reproduction in commercial and professional environments. Featuring a modular design with a combination of high-frequency and low-frequency drivers, it delivers clear, detailed sound with robust power handling. Its sleek, unobtrusive form factor allows for seamless integration into various interior aesthetics while providing exceptional acoustic performance.

Audio Performance

Rated Power

100 W

RMS Power

300 W

Max Power

Frequency Range	80Hz - 20KHz
Sensitivity	96 dB
Maximum SPL	105dB / 119dB (Peak)
Nominal Impedance	4 OHM

Technical Specifications

High Frequency Driver	8 x 1" Driver, 0.8" VC
Low Frequency Driver	4 x 4" Driver, 1" VC
Connectors	Side connectors, Push connectors (top holder)

Dimensions and Logistics

Container Capacity

Container Type	Quantity
20'	620
40'	1300
40' HC	1520

Dimensions (WxDxH)	210 x 170 x 553 mm
--------------------	--------------------

Net Weight	6 Kg
------------	------