

Circuit Breaker Auxiliary and Alarm Contact Module

This module provides auxiliary and alarm contacts for molded case circuit breakers. It allows for remote monitoring of the circuit breaker status and signaling of fault conditions.



ADDITIONAL IMAGES



Product Overview

Auxiliary and Alarm Contact Module

This auxiliary and alarm contact module is designed to enhance the functionality of Moulded Case Circuit Breakers (MCCB). It enables automatic control of auxiliary circuits and provides critical status signaling, including open/closed positions and fault indication. This module is essential for remote monitoring and control applications in electrical systems.

Technical Specifications

Available Contact Configurations

- 1 N/O and 1 N/C + 1 alarm contact
- 2 N/O and 2 N/C + 1 alarm contact

Compatibility

Compatible Circuit Breaker Series

Series Group 1	Series Group 2	Series Group 3
CM1-63FB, CM1, TM30(NF30), CDM1-63A	CM 1-100FB, CM1, TM30(NF30), CDM1-100A	CM 1-225FB, CM1, TM30(NF30), CDM1-225A
CM1-400FB, CM1, TM30(NF30), CDM1-400	DAM1-250/400FB, DAM1-250A, 400A	DZ20-100FB, DZ20-100A
DZ20-225FC, DZ20-225A	-	-

Operational Information

Wiring Logic

MCCB State	Explanation
Close position	Us1 is auxiliary power, Us2 is alarm power
Open position	Us1 is auxiliary power, Us2 is alarm power

Logistics & Terms

Standard Delivery Time	25 days upon receipt of order confirmation
Accepted Payment Terms	TT (30% deposit, 70% balance against BL), L/C at sight
OEM Availability	Yes