

Column Line Array Loudspeaker

This column loudspeaker features a direct drive unit for focused sound projection. Its slim profile is designed for wall mounting and optimized for clarity in acoustically challenging spaces.



Overview

Professional Column Line Array

This column line array loudspeaker is engineered for high-performance commercial sound reinforcement. Featuring a robust two-way frequency design and premium birch plywood construction, it delivers clear, consistent audio projection. Its ultrathin, ergonomic design allows for flexible installation, making it an ideal choice for professional venues requiring reliable and aesthetically discreet audio solutions.

Acoustic Performance

Sound Pressure Levels

110 dB

Continuous SPL

115 dB

Maximum SPL

Frequency Response

80Hz - 20KHz (± 3 dB)

Sensitivity

92 dB

Directivity

100° Horizontal x 60° Vertical

Power & Connectivity

Power Handling

300 W

RMS Power

600 W

Peak Power

Impedance

8 Ω

Connectors

2x NL4 Speakon

Drivers

Driver Configuration

Driver Type	Specification
High Pitch	Silk Ribbon (40W)
Low Pitch	4" x 2 (100mm)
Alto Pitch	5" x 2 (130mm)

Physical & Installation

Installation

- 4x M8 Wall-mounting hidden installation
- Integrated embedded handle

Cabinet Material	18mm High-quality Birch Plywood
-------------------------	---------------------------------

Dimensions (W x H x D)	149 x 698 x 150 mm
-------------------------------	--------------------