

Commercial Beverage Dispenser

This beverage dispenser is designed for dispensing a variety of cold beverages such as juices, iced tea, and lemonade. It features transparent bowls, each with its own dispensing tap and agitator to maintain consistent mixing and prevent settling.

LRS19Lx2

Parameters

Voltage : 220-240V / 110-115V
 Frequency : 50/60Hz
 Power : 280W
 Power : 800W
 Temperature: 7°C - 12°C
 Temperature: 52°C - 58°C
 Size : 330L*390W*670H(mm)
 Size : 360L*450W*700H(mm)
 Weight : 24kg
 Weight : 27kg



ADDITIONAL IMAGES

LSP9Lx3

Parameters

Voltage : 220-240V / 110-115V
 Frequency : 50/60Hz
 Power : 280W
 Power : 800W
 Temperature: 7°C - 12°C
 Temperature: 52°C - 58°C
 Size : 410L*450W*670H(mm)
 Size : 490L*550W*700H(mm)
 Weight : 27kg
 Weight : 29kg



Product Overview

Professional Beverage Dispensing Solution

This versatile beverage dispenser features a European design, constructed with a high-quality stainless steel body for durability and a professional appearance. The transparent, unbreakable PC material tanks allow for clear product visibility, while the reliable compressor system uses environmentally friendly R134a refrigerant. Designed for commercial environments, it offers precise temperature control for both cold and hot beverages, ensuring consistent quality and easy maintenance.

Technical Specifications

Cooling Temperature Range

7 °C

Min Temp

12 °C

Max Temp

Heating Temperature Range

52 °C

Min Temp

58 °C

Max Temp

Power Consumption

- 280
- 800

Supported Voltage

220-240V, 110-115V

Frequency

50/60Hz

Model Comparison

Model Dimensions and Weight

Model Type	Dimensions (mm)	Weight (kg)
Double Bowl (LRSJ9Lx2)	330L*390W*670H	24
Double Bowl (LRSJ9Lx2)	360L*450W*700H	27
Triple Bowl (LSP9Lx3)	410L*450W*670H	27
Triple Bowl (LSP9Lx3)	490L*450W*700H	29

Construction Materials

Materials

Stainless Steel Body • PC Material Tanks

Refrigerant

R134a