

Compact Excavator with Zero Tail Swing

This compact excavator is designed for digging, lifting, and grading tasks in confined spaces. It features a zero tail swing radius for enhanced maneuverability and safety on various job sites.



ADDITIONAL IMAGES



Overview

Compact Power and Precision

This compact excavator features a zero tail swing radius, providing exceptional maneuverability and safety within confined urban or landscaping environments. Engineered for efficiency, the machine utilizes a robust hydraulic system to deliver high-performance digging and lifting capabilities. With a comfortable operator station and intuitive controls, it ensures enhanced productivity and ease of use during demanding earthmoving tasks.

Performance Metrics

Maximum Digging Force

21.5 kN

Digging Force

Maximum Traction	28.1 kN
Maximum Gradeability	e58% (30°)

Hydraulic System

Operating Hydraulic Pressure	20.6 Mpa
Variable Displacement Pump Capacity	16.1+16.1+7+3.5 ml/r

Operational Capabilities

Travelling Speed Range	2.6 - 4.1 km/h
Platform Swing Speed	10.8 rpm
Digging Arm Swing Angularity (Left/Right)	50°/80°

General Features

Core Features

Zero Tail Swing, Compact Design, Hydraulic Pilot Controls, Rubber Track Undercarriage