

Countersink Bit

This is a high-speed steel (HSS) countersink with a 60-degree countersink angle and three cutting edges. It features a tin-coated surface treatment for enhanced durability and performance.

COUNTERSINK

32707 高硬度鋼 HSS countersink 60° WITH THREE CUTTING EDGES

- 材料: HSS
- 角度: 60°
- 刃數: 3
- 表面處理: 鍍錫

● 材料: HSS
● 角度: 60°
● 刃數: 3
● 表面處理: 鍍錫

Flute Diameter (D)	Shank Diameter (d)	Total Length (L)
6.3	5	45
8	6	50
10	6	53
12.5	8	56
16	10	63
20	10	67
25	10	71

Product Overview

High-Performance HSS Countersink Bit

This professional-grade countersink bit is engineered from high-speed steel (HSS) for superior durability and cutting efficiency. Designed with a 60-degree countersink angle and three precision cutting edges, it ensures clean, accurate finishes on a variety of materials. The surface is enhanced with a TiN (Titanium Nitride) coating, significantly extending tool life and improving performance under demanding conditions.

Technical Specifications

Surface Treatment	
TiN-Coated	
Material	High-Speed Steel (HSS)
Countersink Angle	60 °
Number of Cutting Edges	3

Size Specifications

Size Dimensions Table

Flute Diameter (D)	Shank Diameter (d)	Total Length (L)
6.3	5	45
8	6	50
10	6	53
12.5	8	56
16	10	63
20	10	67
25	10	71