

CR2450 Lithium Coin Cell Battery

The CR2450 is a 3V lithium coin cell battery. It features a nominal capacity of 600mAh and an operating temperature range of -20 to 70 .



Overview

High-Performance CR2450 Lithium Coin Cell

This CR2450 lithium manganese dioxide coin cell battery is engineered for professional electronic applications requiring a reliable and consistent power source. With a 3V nominal voltage and a 600mAh capacity, it provides long-lasting energy for demanding devices. The battery is designed for stability across a wide temperature range and features robust leakage resistance for safe operation.

Electrical Specifications

Nominal Voltage	3 V
Nominal Capacity	600 mAh
Operating Temperature Range	-20 to 70

Physical Dimensions

Dimensions

24.5 mm
Diameter

5 mm
Height

Approximate Weight	6.6 g
--------------------	-------

Performance Data

Minimum Average Duration (7.5k@oad)

Test Condition	Duration
Initial Test (New battery)	1450h
After 12 Months	1370h

Voltage Stability

Parameter	Initial (V)	After 12 Months (V)
Open Circuit Voltage	3.10 - 3.45	3.10 - 3.45
Closed Circuit Voltage (7.5k@)	3.10 - 3.45	3.00 - 3.45

Quality & Compliance

Quality Features	No Leakage, High Temperature Resistance, Smooth Appearance, Clear Marking
------------------	---