

# Cylindrical LED Surface-Mounted Spotlight

This surface-mounted LED spotlight features a cylindrical head for focused illumination. It is designed for easy installation on ceilings or walls, providing a modern aesthetic.



## ADDITIONAL IMAGES

**LED surface-mounted spotlights**

**Model NO.:** LBS2457M  
**Material:** Aluminium  
**Power:** 30W  
**Input voltage:** AC220-240V  
**CCT:** 2700K/3000K/4000K/5000K for option  
**Lumens:** 2700 lm @ 3000K @ 24°  
**Ra:** 80  
**Beam angle:** 15° / 24° / 38° / 60°  
**LED:** Cree  
**Driver:** Engerlobe  
**Product certification:** CE  
**Product certification:** White/Black  
**Product size:** Ø65\*H1236mm

**Light distribution curve**

Beam angle	15°	24°	38°	60°
Beam diameter	1.1m	1.5m	2.1m	3.5m
Beam diameter	1.1m	1.5m	2.1m	3.5m
Beam diameter	1.1m	1.5m	2.1m	3.5m
Beam diameter	1.1m	1.5m	2.1m	3.5m

## Overview

### Professional Surface-Mounted Spotlight

This high-performance cylindrical LED spotlight is engineered for versatile indoor lighting applications, from accentuating architectural features to providing general illumination. Constructed from durable aluminium, it offers a sleek, minimalist aesthetic suitable for both residential and commercial environments. The fixture features a fully adjustable head with 350° rotation and vertical mobility, allowing for precise light direction. With multiple beam angle options and color temperature settings, it provides a customizable lighting solution for any professional space.

## Technical Specifications

Power Consumption	30 W
Input Voltage	AC220-240V
Color Rendering Index (Ra)	80
Dimensions	Ø65x H236mm

## Lighting Performance

### Luminous Flux

**2700 lm**  
Output

### Available Beam Angles

- 15°
- 24°
- 38°
- 60°

### Color Temperature Options

2700K, 3000K, 4000K, 5000K

## Design & Features

### Available Finishes

White • Black

### Adjustability

Up-down moveable and 350° rotation

### Housing Material

Aluminium

## Compliance

### Certifications

CE, RoHS