

Diesel Water Pump 3-Inch 30 m³/h

This single-cylinder diesel water pump has a 3-inch suction/discharge port diameter and a flow capacity of 30 m³/h. It has a maximum suction head of 8 meters and a continuous output of 4.0 kW.



ADDITIONAL IMAGES



Product Overview

Industrial Diesel Water Pump

This high-performance 3-inch diesel water pump is engineered for efficient water transfer in professional environments like agriculture and construction. With a flow capacity of 30 m³/h and a reliable 4.0 kW output, it is built to handle demanding fluid management tasks. Designed for durability and ease of use, it features a self-priming mechanism for quick startup and stable operation.

Performance Specifications

Key Performance Indicators

30 m³/h

Flow Capacity

13 m

Continuous Head

4 kW

Continuous Output

Technical Details

Technical Data

Feature	Value
Port Diameter	3 inches
Max Suction Head	8 meters
Self-priming time	120 s/4m

Operation and Maintenance

Operation Guidelines

- Break-in period: Run at low speed/load for first 20 hours
- Fuel type: Light diesel fuel
- Lubrication: Use CC or CD classification oil
- Stop engine completely before refueling

Safety Warnings

Operational Safety

Ventilation Required, Flammable Fuel, No Smoking or Fire, Poisonous Exhaust