

Digital AdBlue Flow Meter

This digital flow meter is designed for measuring flow rates between 20 and 120 liters per minute. It features a digital display showing the flow rate and total volume.



ADDITIONAL IMAGES



Product Overview

Professional Digital Flow Measurement

The FM-200 is a versatile digital flow meter engineered for precision monitoring of AdBlue (Diesel Exhaust Fluid), water, chemicals, diesel, and kerosene. Designed for industrial reliability, it features a clear digital interface that tracks both real-time flow rates and cumulative totals. This self-ventilated unit is ideal for professional applications requiring accurate fluid management and continuous duty performance.

Performance Metrics

Performance Highlights

120 L/min
Max Flow Rate

20 L/min
Min Flow Rate

220 V AC
Operating Voltage

Technical Specifications

Electrical Requirements

Parameter	Value
Voltage	220V AC
Current	2A
Rated Flow	40L/min

Flow Rate Range	20 - 120 L/min
-----------------	----------------

Compatibility & Usage

Compatible Fluids	AdBlue, Diesel Exhaust Fluid (DEF), Urea Solutions, Water, Chemicals, Diesel, Kerosene
-------------------	--

Operational Features

Control Functions

- On/Clear function
- Setup configuration
- Total volume display
- 3-second safety press to activate functions

Duty Cycle

Continuous Duty

Ventilation Type

Self Ventilated

Compliance

Certifications

CE