

Digital Satellite Finder with 3.5" LCD Screen

This digital satellite finder has a 3.5" TFT LCD screen. It supports DVB-S/S2 and CCTV camera testing.



ADDITIONAL IMAGES



Product Overview



High-resolution display showing real-time signal analysis and menu interface.

Professional Satellite & CCTV Testing

This handheld digital satellite finder is an essential tool for the installation and maintenance of satellite TV systems. Featuring a 3.5-inch TFT LCD screen, it provides real-time signal measurements and supports DVB-S/S2 standards. Beyond satellite alignment, the device offers versatile functionality including CCTV camera testing for AHD, TVI, CVI, and CVBS formats, making it a comprehensive solution for field technicians.

Technical Specifications

Frequency Range	950 MHz - 2150MHz
Input Level	-65 to -25dBm
Input Impedance	75 Ω
Supported Standards	DVB-S, DVB-S2, AHD, TVI, CVI, CVBS

Display & Interface

UI Features

- Multi-lingual OSD
- User-friendly UI
- Real-time constellation display
- Spectrum analyzer function

Screen Size	3.5 inch
-------------	----------

Display Type	TFT LCD
--------------	---------

Power & Connectivity

Connectivity

- CCTV IN
- RF IN
- USB 2.0
- HDMI

Battery Capacity	2200 mAh
------------------	----------

Power Input	DC 14V / 2A
-------------	-------------

Certifications

Compliance

CE • FC