


Double-Sided LED Sign

This double-sided LED sign is designed for versatile display applications. It features front service access for easy maintenance and is available in various pixel pitches.



ADDITIONAL IMAGES



Overview

High-Performance Double-Sided Outdoor LED Display

This P10 outdoor LED screen features a double-faced design, making it an ideal freestanding solution for high-visibility advertising. Engineered for durability and ease of use, it supports front-service access for simplified maintenance in various outdoor environments. With high brightness levels and a wide viewing angle, it ensures your content remains clear and impactful even in direct sunlight.

Key Performance Metrics

Performance Highlights

7500 cd/m²
Brightness

1000 Hz
Refresh Rate

100000 Hours
Life Span

Display Specifications

Pixel Pitch	10 mm
Physical Density	10000 pixels/m ²
LED Arrangement	DIP346
Viewing Angle (H/V)	120° / 60°

Module & Cabinet Details

Module Specifications

Feature	Value
Module Dimension	160x160 mm
Module Resolution	16x16 pixels
Cabinet Dimension	1280x480 mm
Cabinet Resolution	128x48 pixels

Cabinet Weight	70 kg/m ²
----------------	----------------------

Power & Environment

Power Consumption

Type	Value
Max Power Consumption	700w/m ²
Average Power Consumption	300w/m ²

Ingress Protection

IP65

Operating Temperature	-10° to 45°C
-----------------------	--------------

Connectivity

Supported Signal Inputs	Composite, S-Video, Component, VGA, DVI, HDMI, SDI, HD SDI
-------------------------	--

Scan Method	1/4
-------------	-----