

Double-Wall Electric Hot Water Boiler Urn

This electric hot water boiler features a double-wall stainless steel construction with a visible water gauge. It offers adjustable temperature control from 30 to 110, automatic shut-off, and keep-warm functions for safe and efficient operation.



ADDITIONAL IMAGES



Product Overview

Professional Double-Wall Electric Water Boiler

This high-capacity electric water urn is engineered for commercial environments like hotels and restaurants, featuring a double-wall construction for superior insulation and energy efficiency. It combines a durable SUS 304 stainless steel inner tank with a sleek SS201 outer shell, ensuring both hygiene and longevity. With adjustable temperature controls and multiple safety protections, it provides a reliable and safe solution for large-scale hot water requirements.

Performance & Capacity

Key Performance Metrics

110 °C

Max Temperature

2000 W

Max Power

35 L

Max Capacity

Technical Specifications

Model Specifications Table

Capacity (L)	Power (W)	Voltage (V)	Weight (KG)
11	1500	220	3
12	1500	220	3.3
15	1500	220	3.5
20	1500	220	4
30	2000	220	4.5
35	2000	220	6

Construction & Design

Material Composition

- Inner Tank: SUS 304 Stainless Steel
- Outer Shell: SS201 Stainless Steel
- Liner Thickness: 0.4mm
- Stainless steel tap and cover with safety lock
- Plastic base with integrated maintenance window

Safety & Control

Safety & Control Systems

Automatic Shut-off, Keep-Warm Feature, Double Overheat Protection, Adjustable Temperature (30°C-110°C), Viewable Water Gauge

Maintenance & Service

Maintenance Design

- Detachable heating plate for easy cleaning
- Central maintenance window in base
- Replaceable wearing parts (thermostat, switch, handles)

Service Capabilities

B2B Service Support

ODM Project Support • One-Stop Sourcing • Factory Audit Assistance • Logistic Services • Pre-shipment Inspection