

Dry Powder Filling Machine

This dry powder filling machine ensures precise and efficient filling of dry powder materials. It offers adjustable filling speeds and high accuracy for consistent results.

自动型灭火器干粉灌装线
Automatic fire extinguisher powder filler

技术参数

灌装精度: 1kg ± 0.02
 灌装速度: 6-12kg/min
 电压: AC180V/AC220V 50Hz
 功率: 0.55kW/1.5kW
 重量: 200kg
 体积: 长x宽x高
 1130x520x1350mm

PARAMETERS

Filling precision: 1kg ± 0.02
 Filling speed: 6-12kg/min
 Voltage: AC180V/AC220V 50Hz
 Power: 0.55kW/1.5kW
 Weight: 200kg
 Volume: length x width x height
 1130x520x1350mm



MH19-13

ADDITIONAL IMAGES



高精度灭火器快速灌装生产线 MH19-12
High-precision fire extinguisher fast filling production line

技术参数

灌装精度: 1kg ± 0.015
 灌装速度: 4-12kg/min
 电压: AC220V 50Hz
 功率: 0.55kW
 重量: 100kg
 体积: 长x宽x高
 800x400x1220mm

PARAMETERS

Filling precision: 1kg ± 0.015
 Filling speed: 4-12kg/min
 Voltage: AC220V 50Hz
 Power: 0.55kW
 Weight: 100kg
 Volume: length x width x height
 800x400x1220mm



干粉灌装线
Dry powder filling machine

技术参数

灌装精度: 1kg ± 0.015
 灌装速度: 4-12kg/min
 电压: AC220V 50Hz
 功率: 0.55kW
 重量: 100kg
 体积: 长x宽x高
 800x400x1220mm

PARAMETERS

Filling precision: 1kg ± 0.015
 Filling speed: 4-12kg/min
 Voltage: AC220V 50Hz
 Power: 0.55kW
 Weight: 100kg
 Volume: length x width x height
 800x400x1220mm

Overview

High-Precision Dry Powder Filling Solutions

These professional-grade dry powder filling machines are engineered for precise and efficient material handling, specifically optimized for fire extinguisher maintenance and production. Available in multiple configurations, these units deliver consistent filling accuracy and reliable throughput. Whether you require a compact unit for standard operations or a high-capacity production line, these machines provide the versatility needed for various industrial filling applications.

Model Comparison

Technical Specifications by Model

Model	Filling Precision	Filling Speed	Power Rating	Weight
MH19-11	1kg d ±0.015	6-12 kg/min	0.55 kW	100 kg
MH19-12	±1.5% - ±4%	9 pcs/min (4kg)	3 kW	N/A
MH19-13	1kg d ±0.02	6-12 kg/min	0.55 / 1.5 kW	200 kg

Operational Requirements

Power Supply	AC220V, AC380V, 50Hz
Driving Gas (Model MH19-12)	Dry and clean compressed air: 0.6 to 0.8Mpa

Performance Metrics

Performance Highlights

12 kg/min
Max Filling Speed

3 kW
Max Power