

Evaporative Air Cooler with Remote Control

This multi-purpose machine provides cooling, humidification, and air purification. It features a centrifugal wind wheel for large airflow and low noise, along with a remote control for convenient operation.



ADDITIONAL IMAGES




Product Overview

Versatile 3-in-1 Cooling Solution

This evaporative air cooler combines cooling, humidification, and air purification into a single, energy-efficient unit. Designed for areas between 5-10m², it features a pure copper motor and a centrifugal wind wheel for powerful yet quiet airflow. With intelligent remote control and multiple wind modes, it offers a customizable and convenient cooling experience for professional and domestic environments.

Technical Specifications

	<table border="1"> <tbody> <tr><td>Model No.</td><td>WJD680F-1L</td></tr> <tr><td>Power</td><td>75W</td></tr> <tr><td>Voltage</td><td>220V, 110V</td></tr> <tr><td>Frequency</td><td>50Hz, 60Hz</td></tr> <tr><td>Water tank capacity</td><td>5L</td></tr> <tr><td>Airflow</td><td>500m³/h</td></tr> <tr><td>Timer</td><td>0.5-7.5 hours</td></tr> <tr><td>Product size (with casters)</td><td>335*287*109mm</td></tr> <tr><td>Packing size</td><td>335*287*109mm</td></tr> <tr><td>Gross weight</td><td>6kg</td></tr> <tr><td>Net weight</td><td>5kg</td></tr> <tr><td>Loading Qty</td><td>20/20P, 40/40P, 100/50Pcs</td></tr> <tr><td>Speed</td><td>3 speeds</td></tr> <tr><td>Wind mode</td><td>Natural, Sleep, Standard wind</td></tr> <tr><td>Control panel</td><td>Remote control</td></tr> <tr><td>Style of swing (Mode)</td><td>Up-down, Manual, Left/Right, Automatic</td></tr> <tr><td>Application area</td><td>5-10m²</td></tr> <tr><td>Remote control</td><td>YES</td></tr> <tr><td>Draw out water tank</td><td>YES</td></tr> <tr><td>Deodorizer</td><td>YES</td></tr> <tr><td>Packing carton</td><td>Standard Kraft carton (5 layers)</td></tr> <tr><td>Certification</td><td>ISO9001, ISO14001, CE, BSMI, LVD, CB</td></tr> </tbody> </table>	Model No.	WJD680F-1L	Power	75W	Voltage	220V, 110V	Frequency	50Hz, 60Hz	Water tank capacity	5L	Airflow	500m ³ /h	Timer	0.5-7.5 hours	Product size (with casters)	335*287*109mm	Packing size	335*287*109mm	Gross weight	6kg	Net weight	5kg	Loading Qty	20/20P, 40/40P, 100/50Pcs	Speed	3 speeds	Wind mode	Natural, Sleep, Standard wind	Control panel	Remote control	Style of swing (Mode)	Up-down, Manual, Left/Right, Automatic	Application area	5-10m ²	Remote control	YES	Draw out water tank	YES	Deodorizer	YES	Packing carton	Standard Kraft carton (5 layers)	Certification	ISO9001, ISO14001, CE, BSMI, LVD, CB
Model No.	WJD680F-1L																																												
Power	75W																																												
Voltage	220V, 110V																																												
Frequency	50Hz, 60Hz																																												
Water tank capacity	5L																																												
Airflow	500m ³ /h																																												
Timer	0.5-7.5 hours																																												
Product size (with casters)	335*287*109mm																																												
Packing size	335*287*109mm																																												
Gross weight	6kg																																												
Net weight	5kg																																												
Loading Qty	20/20P, 40/40P, 100/50Pcs																																												
Speed	3 speeds																																												
Wind mode	Natural, Sleep, Standard wind																																												
Control panel	Remote control																																												
Style of swing (Mode)	Up-down, Manual, Left/Right, Automatic																																												
Application area	5-10m ²																																												
Remote control	YES																																												
Draw out water tank	YES																																												
Deodorizer	YES																																												
Packing carton	Standard Kraft carton (5 layers)																																												
Certification	ISO9001, ISO14001, CE, BSMI, LVD, CB																																												

Detailed technical parameters including dimensions, power consumption, and loading quantities.

Rated Power	75 W
Voltage Support	110V, 220V
Frequency	50Hz, 60Hz

Performance

Performance Metrics

500 m³/h
Airflow

5 L
Tank Capacity

10 m²
Max Area

Operation & Control

Wind Modes

- Natural wind
- Sleep wind
- Standard wind

Control Features

- LED Display
- Intelligent Remote Control
- Button-type Control Board
- 0.5 - 7.5 Hour Timer

Swing Mechanism

Manual Up-Down; Automatic Left-Right

Physical Attributes

Weight

Type	Weight
Net Weight	5 kg
Gross Weight	6 kg

Product Dimensions

300 x 245 x 670 mm

Logistics & Manufacturing

Container Loading Quantity

Container Type	Quantity
20'GP	470 pcs
40'HQ	1050 pcs

Certifications

ISO 9001 • ISO 14001 • CE • EMC • LVD • CB

OEM/ODM Available

Yes