

# Four-Wheel Agricultural Tractor

This four-wheel tractor is designed for agricultural applications. It features a robust chassis, reliable engine, and a three-point hitch system.



## ADDITIONAL IMAGES



## Overview

### Versatile Agricultural Performance

This four-wheel agricultural tractor is engineered for demanding farming environments, offering a robust chassis and reliable power for plowing, tilling, and planting tasks. Designed for open-air operation, it features a durable Yunnei 4-cylinder engine and a flexible 8F+2R gear configuration to handle various field conditions. With its three-point linkage system and versatile hydraulic controls, this tractor provides the essential utility needed for efficient farm management.

## Engine & Performance

配套动力 MATCHED POWER	离合器型式 CLUTH TYPE	/	干式、单作用 (可选双作用) DRY-TYPE, SINGLE-ACTING (OPTIONAL DOUBLE-ACTING)				
	发动机 ENGINE	/	云内国四四缸 (III) YUNNEI 4 CYLINDER				
	转速 RATED SPEED	r/min	2400				
工作部分 WORKING PORTING	档位 GEAR	/	8F+2R (可选8F+8R) (OPTIONAL 8F+8R)				
	动力输出轴型式 PTO TYPE	/	6键、Φ35、I型 (可选8键) 6 PIN, Φ35, I TYPE (OPTION: 8PIN)				
	动力输出功率 PTO RATED POWER	kW	≥25.1	≥28.2	≥31.3	≥25.1	≥28.2
	动力输出轴转速 PTO SPEED	r/min	760 (可选540/720) (OPTIONAL 540/720)				

Detailed engine and power take-off specifications for optimized field performance.

### PTO Specifications

**760 r/min**

PTO Speed

**31.3 kW**

Max PTO Power

Engine Type

Yunnei 4-cylinder (National III)

Rated Speed

2400 r/min

## Transmission & Drivetrain

Gear Configuration	8F+2R (Optional 8F+8R)
Clutch Type	Dry-type, single-acting (optional double-acting)

## Hydraulic System

液压系统 HYDRAULIC SYSTEM	悬挂装置 THREE POINT LINKAGE	/	后置, 三点悬挂, 1类 REAR, THREE-POINT SUSPENSION ,CAT1					
	液压输出 HYDRAULIC OUTPUT	/	1期液压输出 (可选2档, 简单输出, 无输出) 1-WAY VALVE (OPTIONAL 2-WAY VALVE OR SIMPLE OUTPUT OR NO)					
	液压调节方式 HYDRAULIC ADJUSTMENT MODE	/	强制液力系统, 位置控制及浮动控制 (可选液力系统) FORCED HYDRAULIC SYSTEM, POSITION CONTROL, FLOATING CONTROL (OPTIONAL: FORCED HYDRAULIC SYSTEM, POSITION CONTRL, FLOATING CONTR)					
	框架中心处最大提升力 MAX.LIFTING FORCE AT FRAME CENTER	kN	27.1	28.0	28.9	27.1	28.0	28.9
轮胎型号 TYRE TYPE	标准轮胎型号(前/后) NORM TYRE SIZE (FRONT/ REAR)	/	6.00-12/9.50-16			4.50-12/9.50-16		
	选装轮胎(1型) OPTIONAL TYRE (1)	/	6.50-12/13.6-16			5.00-12/13.6-16		

Hydraulic adjustment modes and available tire configurations.

Adjustment Modes	Position Control, Floating Control, Forced Hydraulic System
Max Lifting Force	8.9 kN

## Dimensions & Weight

	Model	Unit	KT404-D	KT454-D	KT504-D	KT400-D	KT450-D	KT500-D
整机参数 DIMENSIONS OF TRACTOR	型式 TYPE	/	四轮驱动(4*4) DRIVE TYPE (4*4)			两轮驱动(4*2) DRIVE TYPE (4*2)		
	KW	kW	29.5	33.1	36.8	29.5	33.1	36.8
	外形尺寸(长*宽*高) DIMENSION (L*W*H)	mm	3130*1250*2255					
	轴距 WHEEL BASE	mm	1820					
	离地间隙 MIN.GROUND CLEARANCE	mm	240			265		
	最小使用质量 WEIGHT	kg	1480			1300		
	轮胎 TREAD	mm	前轮胎: 1000(1000 - 1300)可调 后轮胎: 1000(1000 - 1200)可调 FRONT TREAD:1000(1000 - 1300)ADJUSTABLE REAR TREAD:1000(1000 - 1200)ADJUSTABLE					

Physical dimensions and weight specifications across the tractor model series.

<b>Weight</b>	<ul style="list-style-type: none"> <li>1300</li> <li>1480</li> </ul>
<b>Dimensions (L x W x H)</b>	3130 x 1250 x 2255 mm
<b>Wheelbase</b>	1820 mm

## Tires

<b>Standard Tire Sizes</b>	<ul style="list-style-type: none"> <li>6.00-12/9.50-16</li> <li>4.50-12/9.50-16</li> </ul>
----------------------------	--