

FTTH CATV Optical Receiver

This FTTH CATV optical receiver is compatible with GPON and EPON FTTx PON technology. It converts optical signals to RF signals for CATV distribution.



Overview

High-Performance FTTH CATV Receiver

This optical receiver is designed for fiber-to-the-home (FTTH) networks, ensuring seamless compatibility with GPON, EPON, and other FTTx PON technologies. It leverages advanced GaAs MMIC amplifier technology to deliver excellent linearity, flatness, and ultra-low noise performance. Engineered for reliability and ease of installation, this unit provides high-quality video signal distribution over fiber optic infrastructure.

Key Features

Key Features

GaAs MMIC Amplifier, Ultra Low Noise, High Linearity, Excellent Flatness, Compact Design, Wide Input Power Range

Customer Interface

Connectivity

Interface Type	Specification
RF Connector	F-female
Optical Connector	SC/APC or FC/APC
Power Supply	DC2.1

Optical Parameter

Performance Metrics

0.9 A/W

Responsivity

Input Power Range	-10 to +3 dBm
AGC Operation Range	-7 to +2 dBm

Status Indicators

Optical Power LED Logic

- Red: Optical power < -10dBm
- Green: -10dBm < Optical power < +3dBm
- All Lighted: Optical power > +3dBm