

Gasoline Powered Water Pump - 25mm

This gasoline-powered water pump is designed for efficient drainage and irrigation in agricultural applications. The pump is self-priming and capable of delivering high flow rates, making it suitable for a variety of water transfer tasks.



ADDITIONAL IMAGES



Overview

Efficient Agricultural Water Management

This gasoline-powered water pump is engineered for reliable drainage and irrigation tasks in agricultural settings. Featuring a robust engine and durable housing, it delivers consistent performance with a maximum flux of 5m³/h and a lift capacity of 10m. Its compact, portable design ensures easy setup and operation, providing an efficient solution for various water transfer requirements.

Performance Specifications

Maximum Flux

5 m³/h

Maximum Flux

Rated Rotation Speed	3600 rpm
Maximum Lift	10 m
Maximum Suction	6 m
Port Sizes	Inlet: 25mm, Outlet: 25mm

Engine Details

Engine Model	YH152F
Displacement	98 mL
Fuel Tank Capacity	1.4 L
Bore x Stroke	52 x 46
Compression Ratio	5.6:1
Ignition System	Transistor magneto
Starting System	Recoil start

Logistics & Physical

Container Load Capacity

Container Type	Units
20ft	684
40ft	1404

Weight	12/14kg
Dimensions	390 x 300 x 410mm