

Gasoline Powered Water Transfer Pump

This gasoline water pump is designed for efficient water transfer in various applications. Its portable design and durable construction make it suitable for irrigation, construction, and emergency water removal.



ADDITIONAL IMAGES



Overview

High-Performance Gasoline Water Pump

This gasoline-powered water transfer pump is engineered for superior durability and high-efficiency performance in agricultural irrigation and municipal sewage projects. Featuring a reliable four-stroke OHV engine and reinforced air-cooling, it delivers consistent power for demanding water management tasks. The unit is designed with ease of use in mind, offering both manual recoil start and optional key-start capabilities for flexible operation in various environments.

Performance Metrics

Key Performance Metrics

78 m³/h

Max Flow Rate

16 m

General Lift

8 m

Suction Lift

Engine Specifications

Engine Model	GX390
Engine Type	One-Cylinder Reinforced Air-Cooling Four-Stroke OHV
Displacement	389 cm ³
Max Output Power	13 HP
Rotation Speed	3600 RPM

Technical Details

Outlet/Intake Diameter	100mm (4 inch)
Gasoline Tank Capacity	3.6 L
Machine Oil Capacity	0.6 L

Features

Key Features	Recoil Start, Low Noise Muffler, Cast Iron Cam Shaft, High Quality Carburetor, Key Start Optional
--------------	---

Logistics

Dimensions & Weight

Metric	Value
Packing Dimension	65.5 x 45.5 x 58 cm
Gross Weight	47 kg
Net Weight	45 kg