

Gigabit Ethernet Fiber Media Converter

This Ethernet fiber media converter supports 10/100M and 10/100/1000M speeds with IEEE802.3ah OAM manageability. It allows real-time supervision and parameter setting of remote fiber media converters.

Payment
T/T by bank is our preferable payment method
we also accept different payments, such as: LC, Western Union, Paypal and Escrow

T/T LC **WESTERN UNION** **Paypal** **ESCROW**

Shipment
Lead time based on our strong production capacity, normally, the product can ready within 3 days
if the qty of the order is more than 500pcs, maybe we need a little more time
Delivery methods: big order could be by sea or air, small volume could be by Express.
HS CODE: 8517109990

Warranty
All products have been checked and packed in good condition after our serious QC test, if you have any question, pls feel free to contact us, we would get it solved in limited time and our service would make you trust us.
3 years normal warranty is provided

Remark
we answer all your inquiries in 8hours or less, guaranteed, pls feel free to contact us below
TradeManager: traucom
Skype: robot_luz905
Tel: 8620 71 372 0092 or 8620 1881 055582 (24hours for you)
<http://www.t-l.com.cn/>

ADDITIONAL IMAGES



Overview

Gigabit Ethernet Fiber Media Converter

This manageable Ethernet fiber media converter supports 10/100/1000M speeds and features IEEE802.3ah OAM compliance for real-time monitoring of remote devices. Designed to enhance network maintenance and reduce operational expenditure, it provides comprehensive management capabilities including web-based configuration, SNMP monitoring, and VLAN support. It is an ideal solution for operators looking to improve service quality and network visibility.

Key Features

Network & Security

- Loop Detection
- Broadcast/Multicast/Unicast Storm Control
- 16 IEEE 802.1Q VLAN groups
- Q-in-Q VLAN
- 16 TCP/UDP Filter groups

Management Features

Web Interface, SNMP v1/v2c, Remote Management, Firmware Upgrade, Event Traps

Technical Parameters

Ethernet Interface

Parameter	Specification
Standards	IEEE802.3, 802.3u, 802.3z, 802.3ab, 802.3x
Data Rate	10/100/1000 Mbps
Connector	RJ-45
Transmission Distance	100m (UTP CAT5/5E)

Optical Port Specifications

- Connectors: ST, SC, FC, LC
- Multi-mode Wavelengths: 850nm, 1310nm
- Single-mode Wavelengths: 1310nm, 1550nm
- Dual Fiber Distance: Up to 100km
- Single Fiber Distance: Up to 80km

Power Requirements

5 W

Max Power Consumption

Environment & Dimensions

Physical Dimensions	156mm (W) x 128mm (D) x 32mm (H)
Operating Temperature	0°C to +50°C
Storage Temperature	-20°C to +70°C