

HD DVB-S2 Digital Satellite Receiver

This unit is fully compliant with DVB-S/DVB-S2, MPEG-2, MPEG-4, and H.264 standards. It supports PVR recording, enabling simultaneous viewing and recording of different channels, and it can play back JPEG and MP3 files from external storage devices via USB 2.0 or HDD.



Overview

Professional HD Satellite Reception

This HD DVB-S2 Digital Satellite Receiver is a high-performance solution designed for professional-grade signal processing and clear media delivery. Featuring advanced decoding capabilities and robust connectivity, it supports standard and high-definition resolutions up to 1080i. The integration of Conax CAS7.0, Common Interface support, and multiple card slots ensures versatile access and secure signal management for business applications.

Technical Specifications

Processor Performance

266 MHz

Clock Frequency

Memory Capacity

Memory Type	Size
Flash Memory	8M bytes
DDR2 Memory	128M bytes

Video and Audio

Supported Audio Decoders

- MPEG-1 Layer I/II
- MPEG-1 Layer 3 (MP3)
- WMA v.9
- WMA Pro
- DTS

Format Resolutions	1080i, 720p, 576p
--------------------	-------------------

Connectivity and Features

Supported Standards

DVB-S2 • Conax CAS7.0 • Stab-USALS • DiSEqC

Physical Slots and Ports	USB 2.0, Common Interface (CI), Ethernet (Optional), S/PDIF Port, 2 CA Slots
--------------------------	--

Dimensions	290x210x58mm
------------	--------------