


Heat Shrinkable Tubing with Hot-Melt Adhesive

This heat shrinkable tubing provides insulation and protection for electrical connections. It features a hot-melt adhesive for a waterproof seal and enhanced protection in harsh environments.



ADDITIONAL IMAGES



Product Overview

MRA2 Heat Shrinkable Tubing

The MRA2 Heat Shrinkable Tubing is a medium-wall solution designed for electrical insulation and environmental protection. Featuring an integrated hot-melt adhesive lining, it ensures a superior waterproof seal against moisture and corrosion when heated. This tubing is engineered for reliability in demanding applications, offering excellent UV and weathering resistance while maintaining a halogen-free composition.

Technical Specifications

Color

Black

Shrinkage Ratio

3:1

Operating Temperature

-40°C to +90°C

Voltage Rating

Up to 36kV

Wall Type

Medium wall

Standards

IEC 60684

Key Features

Key Features

- Hot-melt adhesive for waterproof sealing
- Excellent corrosion resistance
- UV and weathering resistance
- Halogen-free material
- Superior electrical and mechanical properties

Sizing and Dimensions

Dimensions Table

Type	Expanded (mm)	Recovered (mm)	Wall Thickness (mm)
MRA2 20/5	20	5	2
MRA2 33/8	33	8	2
MRA2 40/12	40	12	2
MRA2 50/16	50	16	2
MRA2 63/19	63	19	2.4
MRA2 75/22	75	22	2.7
MRA2 85/25	85	25	2.8
MRA2 95/29	95	29	3.1
MRA2 115/35	115	35	3.1
MRA2 140/42	140	42	3.1
MRA2 160/50	160	50	3.2
MRA2 180/60	180	60	3.2