

Hydraulic Crimping Head

This hydraulic crimping head delivers a crimping force of 350kN. It is designed for crimping operations on connectors and terminals within a range of 300mm²-1000mm².



Product Overview

Professional Grade Hydraulic Crimping

The T-1000 is a high-performance hydraulic crimping head engineered for heavy-duty electrical infrastructure projects. It provides a significant 350kN crimping force, ensuring reliable and consistent connections for large cross-section conductors. Compatible with a variety of external hydraulic pumps, this tool is ideal for substation maintenance and overhead line construction.

Technical Specifications

Crimping Force

350 kN

Crimping Force

Weight

12 kg

Performance Data

Type	Crimping Shape	Conductor	Crimping Range (mm ²)	Application	Die series
T-1000		Copper	500-1000	JGK	MT
			500-630	JGY	
			500-630	JGA	
			500-1000	GTY-2	
		Aluminium	300-1000	CAL-BS	ML
			300-630	GLM	

Technical performance and die series compatibility guide.

Crimping Capacity

Conductor Material	Range (mm ²)	Die Series
Copper	500-1000	MT
Aluminium	300-1000	ML

Package Information

Included Components

- T-1000 Hydraulic Crimping Head
- Die set
- Manual
- Spare seal ring
- Plastic carry case