

# Hydraulic Distributor Remote Control Joystick

This hydraulic joystick offers precise control and quick response for hydraulic systems. Its ergonomic handle is designed for comfortable operation and minimal effort, with ports arranged for easy installation.



## Product Overview

### Hydraulic Distributor Remote Control Joystick

This compact hydraulic remote control joystick is engineered for precision and rapid response in demanding industrial environments. Featuring an ergonomic handle with customizable switch configurations, it ensures operator comfort and minimal fatigue during extended use. The system supports direct solenoid valve connection for reliable positioning, automated resetting, and superior control over hydraulic cylinder speeds.

## Technical Specifications

### Технические Характеристики:

Давление подачи (мПа)	Максимум 5
Поток (л/мин)	Максимум 16
Обратное давление (мПа)	Максимум 0,3
Рабочий диапазон давления (мПа)	0,5 - 1,95
Электромагнит	
Рабочее напряжение (В)	Постоянное напряжение 24
Ток срабатывания (мА)	200 - 230 (при нормальной рабочей температуре, 24 В)
Рабочая температура (°C)	От -40 до 121

## Performance Metrics

**5 mPa**

Max Supply Pressure

**16 l/min**

Max Flow Rate

**0.3 mPa**

Max Back Pressure

## Electrical Data

Parameter	Value
Operating Voltage	24V DC
Trigger Current	200-230 mA
Operating Temp	-40 to 121 °C

## Key Features

### Operational Advantages

- Compact design for easy installation
- Parallel port arrangement for simplified setup
- Direct solenoid valve compatibility
- Automated reset and positioning mechanism
- Variable secondary pressure control
- Integrated lever arm protection against failures

## Applications

### Compatible Equipment

Loaders, Bulldozers, Lifting Equipment, Agricultural Machinery, Material Handling, Compaction Rollers, Forestry Machinery, Container Cranes, Drilling Rigs