

Hydraulic Press Brake

This hydraulic press brake is used for bending sheet metal and plate. It features a robust frame, hydraulic system, and precision control for accurate and repeatable bends.

WD67K 系列折弯机参数表

型号	80T-3000	100T-2000	100T-3000	125T-4000	160T-4000
总长度 (mm)	800	1000	1000	1250	1600
工作长度 (mm)	3000	3000	4000	4000	4000
回程油缸 (mm)	3000	2500	3100	3100	3100
最大行程 (mm)	95	90	90	90	90
最大行程 (mm)	190	190	190	190	190
最大行程 (mm)	190	190	200	200	200
行程 (mm)	10	10	10	8	8
行程 (mm)	90	70	70	90	80
行程 (mm)	7.5	7.5	7.5	11	11
行程 (mm)	900	900	900	900	900
行程 (mm)	3000	3000	4000	4000	4000
行程 (mm)	1100	1400	1400	1400	1400
行程 (mm)	3500	3500	2700	2700	2700
行程 (mm)	8000	7400	9600	9600	10000

ADDITIONAL IMAGES



Overview

Versatile Metal Forming Solution

The hydraulic press brake is a robust and efficient machine designed for precise sheet metal and plate bending operations. Featuring a heavy-duty frame and a reliable hydraulic system, it ensures accurate and repeatable bends for various industrial applications. Available in multiple configurations ranging from 80T to 160T, these machines are equipped with essential components including precision back gauges, depth calculators, and high-quality bending moulds to meet diverse production requirements.

Key Components

Included Components

Corner Assembly, Back Gauge, Bending Mould, Depth Calculator, Hydraulic Valve, Hydraulic System

Performance Metrics

Key Performance Indicators

160 T

Max Nominal Press Force

4000 mm

Max Table Length

150 mm

Ram Stroke

Technical Specifications

Model Specifications

Model	Nominal Press (KN)	Table Length (mm)	Motor Power (kW)	Weight (kg)
80T/3200	800	3200	7.5	5000
100T/3200	1000	3200	7.5	7400
100T/4000	1000	4000	7.5	9500
125T/4000	1250	4000	11	9800
160T/4000	1600	4000	11	12000

General Operational Parameters

- Max Open Height: 330mm
- Back Gauge Range: 500mm
- Gap Depth: 255mm - 320mm (varies by model)