

Indoor Dome Network Camera

This high-resolution IP camera is designed for surveillance and monitoring applications. It features a dome-shaped enclosure for discreet installation.



Overview

Indoor Dome Network Camera

This indoor dome network camera is designed for reliable surveillance and monitoring applications. It features a compact, ceiling-mount design and supports a wide range of network protocols for flexible integration. With built-in motion detection, audio support, and remote viewing capabilities, it provides a comprehensive security solution for indoor environments.

Physical Specifications

Dimensions	150mm (Ø) x 100mm (H)
Weight	1000 g
Installation	Ceiling Mount

Technical Performance

Resolution Options	D1 (720*576), CIF (320*288), QCIF (176*144)
Compression	MPEG-4
Minimum Illumination	0 LUX (IR on)
Bitrate	16K - 3M

Connectivity & Interfaces

Serial Ports

- RS485 Support
- 1x RS232 Port

Ethernet	RJ45, 10Base-T/100base-TX
I/O Interface	4 input, 1 output

Environmental Requirements

Operating Temperature

0 °C Min Temp	45 °C Max Temp
-------------------------	--------------------------

Operating Humidity	10%-80% non-condensing
--------------------	------------------------

System Compatibility

Supported Operating Systems

Windows 98, Windows 2000, Windows XP, Windows Vista, Windows 7, Mac OS