

Insulated Wire Tension Clamp

This tension clamp is designed to anchor insulated service lines with 2 or 4 conductors. The clamp and wedges are made of high mechanical strength, weather resistant, anti UV material.



ADDITIONAL IMAGES



Overview

High-Performance PA Tension Clamp

The PA tension clamp is expertly engineered to securely anchor insulated service lines featuring 2 or 4 conductors. Constructed from high-mechanical-strength, weather-resistant, and anti-UV materials, it ensures long-term durability in demanding outdoor environments. Its thoughtful design eliminates the need for additional installation tools and prevents loose parts, making it a reliable solution for overhead electrical distribution networks.

Technical Specifications

Type	Conductor Size (mm ²)	Failure Load(kN)	Pack (pcs)
PA25-2x16-25/4x16-25	2x16-4x25	1.9	48
PA25-2x16-25/4x16-25B	2x16-4x25	1.9	60

Technical data overview for PA tension clamp models and packaging quantities.

Performance Metrics

1.9 kN

Failure Load

Model Specifications

Model	Conductor Size	Pack Size
PA25-2x16-25/4x16-25	2x16-4x25 mm ²	48
PA25-2x16-25/4x16-25B	2x16-4x25 mm ²	60

Features & Compliance

Key Features

- Special clip design prevents bail slippage
- Easy installation with no additional tools required
- Secure design prevents loose parts from falling during installation
- Weather-resistant and anti-UV material construction

Compliance Standard

NF C 33-042