

Linkable LED Floodlight with Outlet

This LED floodlight provides powerful and efficient illumination for a variety of applications. It features a durable frame and an integrated outlet for convenient tool usage.



ADDITIONAL IMAGES



Product Overview

Versatile Linkable LED Floodlight

This LED SMD floodlight is a professional-grade lighting solution designed for both indoor and outdoor environments. Constructed with a durable die-casting aluminum body and a tempered glass lens, it ensures reliability in demanding conditions. The unit features an integrated outlet socket for linking multiple lights, making it an ideal choice for construction sites and workshops requiring flexible power distribution.

Technical Specifications



Technical overview of the NJ30W and NJ50W models, including power ratings and construction details.

Performance Metrics

30 W Power (NJ30W)	2700 lm Lumens (NJ30W)	50 W Power (NJ50W)	4500 lm Lumens (NJ50W)
------------------------------	----------------------------------	------------------------------	----------------------------------

Model Comparison

Model	Power	Lumens	IP Rating
NJ30W	30W	2700lm	54
NJ50W	50W	4500lm	54

Electrical & Environmental

Electrical Requirements

- Voltage: AC100-240V 50/60Hz
- Energy Efficiency Class: A+
- Protection Class: I
- Working Temperature: -20°C to 55°C

Features & Construction

Key Features

Die-casting Aluminum Body, Tempered Glass Lens, Outlet Socket for Linking, On/Off Switch, SMD LED Chip

Certifications

Certifications

CE • RoHS