Lithium-Ion Battery Charger 29.2V 18A

This charger is designed for lithium-ion batteries, with an input of 200-240VAC at 50/60Hz and 6A. It provides an output of 29.2V at 18A, and includes LED indicators to display the charging status.

ADDITIONAL IMAGES

Overview

Professional Battery Charging Solution

This high-performance battery charger is engineered for efficient and reliable charging of lithium-ion battery packs. Housed in a durable aluminum alloy casing, it includes an integrated cooling system to maintain optimal operating temperatures. The device features clear LED status indicators for real-time monitoring and is built with essential safety protections against electric shock.

Electrical Specifications

Output Performance

29.2 V	18 A	400 W
Voltage	Current	Power

Input Voltage Range

- 110-132VAC
- 200-264VAC

Compatibility & Usage

Supported Battery Types	Li-ion, LiPo, LiFePO4, Lead Acid
Typical Applications	Electric Motorcycle, Electric Scooter, E-bike

Physical Characteristics

Dimensions	135 x 90 x 50 mm
Net Weight	1.35 kg
Housing Material	Aluminium Alloy

Compliance & Warranty

Certifications CE • RoHS	
Warranty	12 Months

Rooms 05–15, 13A/F South Tower, World Finance Centre, Harbour City, 17 Canton Rd, Tsim Sha Tsui, Kowloon, Hong Kong