

Modular Plastic Conveyor Belt HS-2500E

This modular plastic conveyor belt is designed for candy making and food processing applications. Its modular design allows for easy customization and repair.



ADDITIONAL IMAGES



Overview

Modular Plastic Conveyor Belt HS-2500E

This modular plastic conveyor belt is engineered for high-performance food processing and industrial applications. Featuring a 25.4mm pitch and robust 13mm thickness, it offers reliable operation with a maximum load capacity of up to 1.2 tons per square meter. Designed for versatility, it is compatible with a wide range of materials and operating temperatures, ensuring consistent performance in demanding environments.

Technical Specifications

Pitch	25.4 mm
Belt Thickness	13 mm
Minimum Width	50 mm
Open Area	0 %
Rod Diameter	4.9 mm
Available Materials	PP, POM, PE, PA
Available Colors	White, Blue, Gray, Natural, Dark-brown

Capabilities

Working Temperature

-40 °C
Min Temp

260 °C
Max Temp

Certifications

FDA Approved • EU Compliant

Max Load Capacity

1.2 tons/square meter

Configuration

Sprocket Sizes

- 8T-2R
- 10T-2R
- 12T-2R
- 15T-2R
- 18T-2R
- 20T-2R
- 20T-2R-Split

Belt Features

Feature	Status
Flight	No
Side Guard	No
Curve	No

Applications

Suitable Industries

- Food Processing (Meat, Poultry, Seafood, Bakery, Snack Food, Fruit & Vegetables)
- Automotive
- Tire Manufacturing
- Packaging
- Printing/Paper
- Postal
- Corrugated Cardboard
- Can Manufacturing
- PET Manufacturing
- Textile