

Non-Sparking Adjustable Wrench

This adjustable wrench is die-forged and designed for use in hazardous environments. The opening size can be adjusted to suit different sizes of fasteners.



ADDITIONAL IMAGES



Product Overview

Safety-First Engineering

Designed for critical maintenance in hazardous industrial environments, this adjustable wrench is forged from specialized non-sparking alloys. It is specifically engineered to prevent ignition risks when working near flammable or explosive vapors, making it an essential tool for oil, gas, and petrochemical operations. With high tensile strength and corrosion resistance, it combines safety with professional-grade durability.

Technical Specifications

Key Features

Non-Sparking • Non-Magnetic • Corrosion Resistant • Die Forged

Material Performance

Property	Copper-Beryllium	Aluminum-Bronze
Hardness	35-40 HRC	20-30 HRC
Tensile Strength	1117-1326 N/mm ²	782-989 N/mm ²
Standard	GBEx aC	GBEx aB

Copper-Beryllium Composition

2.3 % Beryllium (Max)	0.5 % Nickel (Max)
---------------------------------	------------------------------

Available Materials

Copper-Beryllium Alloy, Aluminum-Bronze Alloy

Certifications & Compliance

Approvals

- ISO9001:2000
- FM (USA)
- TUV (Germany)
- UKAS (UK)
- ATEX Approved