

Non-Sparking Fire Hydrant Wrench, 59mm, 430mm

This non-sparking fire hydrant wrench is suitable for use in potentially explosive environments. It is widely used in industries such as petrochemical and mining.



ADDITIONAL IMAGES



Product Overview

Professional Non-Sparking Hydrant Wrench

This specialized fire hydrant wrench is engineered for safe operation in hazardous, explosive, and flammable atmospheres. Constructed from high-performance copper-beryllium alloy, it provides essential spark-proof, non-magnetic, and rust-resistant properties. Designed with a 59mm opening and a 430mm handle, it offers the necessary leverage and fit for critical maintenance tasks in petrochemical, mining, and industrial environments.

Technical Specifications

Hydrant Nut Size	59 mm
Overall Length	430 mm

Material Properties

Material Composition

Element	Percentage
Beryllium (Be)	1.8% - 2%
Nickel (Ni)	0.1% - 0.6%
Others	< 0.6%
Copper (Cu)	Rest

Hardness	HB283-365
Breaking Strength	105-120 kgf/mm ²

Key Features

Key Benefits

Spark Proof • Non-magnetic • Rust Resistant

Applications

Suitable Industries

- Petrochemical Industry
- Mining
- Gas Stations
- Railways
- Aerospace
- Pharmaceuticals
- Shipyards
- Laboratories
- Desalination Plants