

Non-Sparking Hammering Box Wrench

This non-sparking box wrench is designed for hammering and high-impact applications in environments where sparks could pose a hazard. It is made from aluminum copper or beryllium copper.



ADDITIONAL IMAGES



Product Overview

Professional Non-Sparking Hammering Wrench

Designed for safety in hazardous environments, these non-sparking hammering box wrenches are essential for industries dealing with flammable liquids or gases. Engineered for durability and high torque, they are suitable for heavy-duty applications in oil and gas, mining, chemical processing, and railroad maintenance. Available in a wide range of sizes, these tools provide a secure grip and reliable performance under impact.

Technical Specifications

Hardness Ratings

25 HRC

Aluminum-Bronze

35 HRC

Beryllium-Bronze

Tensile Strength

Material	Strength Range
Aluminum-Bronze	75-85 kgf/mm ²
Beryllium-Bronze	105-120 kgf/mm ²

Available Surface Finishes

Electrostatic Spraying • Natural Color • Passivation

Material Composition

Aluminum Copper, Beryllium Copper

Availability

Available Sizes (mm)

- 17
- 19
- 22
- 24
- 27
- 30
- 32
- 34
- 36
- 41
- 46
- 50
- 55
- 60
- 65
- 70
- 75
- 80
- 85
- 90
- 95
- 100
- 105
- 110
- 115
- 120
- 125
- 130
- 135
- 140
- 145
- 150
- 185

Compliance & Industry

Certifications

ISO 9001, UKAS

Recommended Industries

Petroleum, Chemical, Power Generation, Railroad, Mining