

PCD Grinding Block for Concrete

This grinding block features polycrystalline diamond segments for concrete floor preparation and coating removal. It is suitable for use with floor grinding machines to ensure efficient material removal and surface leveling.



ADDITIONAL IMAGES



Product Overview

High-Performance PCD Grinding Block

This PCD (Polycrystalline Diamond) grinding block is specifically engineered for heavy-duty concrete floor preparation. Designed to deliver aggressive material removal, it excels at stripping away stubborn coatings such as epoxy, resin, paint, varnish, and thick rubber adhesives. With its durable construction and efficient segment design, it ensures smooth leveling of high spots and provides a long operational lifespan for professional grinding applications.

Technical Specifications

Segment Size	40 x 10 x 14 mm
Segment Quantity	2 count
Materials Used	45# Steel, Alloy, Diamond, PCD

Compatibility & Application

Connection Types

- ~~Æ16mm~~
- ~~Æ20mm~~
- ~~Æ22.23mm~~
- M14
- M16
- 5/8"-11

Suitable for Removing

Epoxy • Resin • Paint • Varnish • VCT Mastic • Black Tar Adhesive • Rubber

Logistics

Monthly Supply Ability

30000 pcs

Pieces per Month

Lead Time

3-7 days after payment