


Perforated Flat Top Modular Conveyor Belt

This perforated flat top modular conveyor belt is designed for fruit and vegetable processing. It is constructed from food-approved materials and allows for easy cleaning.



ADDITIONAL IMAGES



Overview

High-Performance Modular Conveyor Belt

This perforated flat-top modular plastic conveyor belt is engineered for demanding industrial environments, particularly in food and vegetable processing. Its durable construction offers excellent resistance to wear and temperature fluctuations, while the modular design allows for easy customization, assembly, and maintenance. Designed with a 17.6% open area to facilitate drainage and airflow, this belt ensures reliable, hygienic transport with a high load capacity of up to 1.2 tons per square meter.

Technical Specifications

Maximum Load Capacity

1.2 tons/m²
Max Load

Pitch	50.8 mm
Thickness	16 mm
Minimum Width	151.5 mm
Open Area	17.6 %
Rod Diameter	5.8 mm
Working Temperature	-40°C to 260°C

Design & Features

Available Colors

White • Blue • Gray • Nature • Dark-brown

Key Features

- Floating in water
- Food defrosting capability
- Maintenance-free design
- Easy to clean
- Side guard available
- Flight available

Materials

PP, POM, PE, PA

Compatibility

Sprocket Dimensions

Sprocket Type	Bore Type
6T, 8T, 10T, 12T	Square & Round
6T-N, 8T-N, 10T-N, 12T-N	Square & Round

Compliance

Certifications

FDA, EU

Applications

Suitable Industries

- Meat (beef & pork)
- Poultry
- Sea Food
- Bakery
- Snack Food
- Fruit & Vegetables
- Automotive
- Tire Manufacturing
- Packaging
- Printing/Paper
- Postal
- Corrugated Cardboard
- Can Manufacturing
- PET Manufacturing
- Textile