

Primerless Polyurethane Windshield Sealant

This primerless polyurethane sealant is designed for windshield bonding and sealing applications. It provides a durable, flexible, and waterproof seal, ensuring long-lasting protection against environmental elements.



ADDITIONAL IMAGES



Product Overview

Professional Grade Windshield Sealant

This high-performance polyurethane sealant is engineered specifically for OEM and aftermarket windshield bonding applications. It features a primerless formula that ensures excellent adhesion to glass and metal surfaces, streamlining the installation process. The resulting bond is both durable and flexible, offering superior resistance against environmental elements and weathering.

Physical and Chemical Properties

Performance Metrics

45 HA

Hardness

4 Mpa

Breaking Strength

350 %

Breaking Elongation

Material Specifications

Property	Value
Skim time	20-60 min
Solid rate	e 2.5nm/24h
Density	1.25 ± 0.15 g/cm ³
Flow rate	20-40 g/min
Solid content	95%

Packaging and Logistics

Packaging Options

- Aluminum Barrel (310ml)
- Soft Package (310ml, 400ml, 600ml)
- Big Barrel (55 gallon)

Storage Requirements

Store in cool place, Keep dry, Avoid direct sunshine, Avoid fire, No collision

Guarantee Period

6-9 months depending on packaging type