

Recirculating Water Chiller

This recirculating chiller provides an economic and environmentally-friendly cooling solution for diverse applications. The thermolysis-type industrial chiller features a radiating capacity of 50W/°C and ensures efficient heat dissipation.



Product Overview

Compact Cooling Solution

This compact recirculating minichiller is an economic and environmentally-friendly cooling solution designed for various laboratory applications. It features a robust design containing a water tank, circulating pump, heat exchanger, and fan to ensure efficient heat dissipation. Built for reliability, this unit offers energy-saving operation and a long service life, making it a dependable choice for professional environments.

Performance Specifications

Radiating Capacity

50 W/°C

Radiating Capacity

Maximum Flow Rate	10L/min / 2L/min
Maximum Lift	10m / 70m
Tank Capacity	9 L

Electrical & Compliance

Certifications

CE • RoHS

Supported Voltage	110V, 220V
Frequency	50/60Hz

Physical Attributes

Weight

Type	Weight
Net Weight	9.5 kg
Gross Weight	12 kg

Product Dimensions (L x W x H)	49 x 27 x 38 cm
Packing Dimensions (L x W x H)	59 x 39 x 48 cm

Features

Key Features

- Energy-saving operation
- Long working life
- Simple operation
- Integrated water flow alarm
- Over-temperature alarm functions