

# Reinforced Grinding Wheel for Stone

This reinforced grinding wheel is designed for stone grinding applications. It has dimensions of 230x6.0x22.2 mm (9"x1/4"x7/8") and a maximum RPM of 6600.



## Product Overview

### High-Performance Stone Grinding

This reinforced grinding wheel is specifically engineered for heavy-duty stone grinding applications. Designed for safety and durability, it adheres to international EN 12413 standards and ISO 9002 quality certifications. It features a Type 27 depressed center profile, providing optimal performance and efficiency for professional stone fabrication tasks.

## Certifications & Standards

**Compliance** EN 12413, ISO 9002, Type 27

## Technical Specifications

### Maximum Linear Speed

**80 m/s**  
Max Speed

### Available Sizes & Performance

Item Number	Dimensions (mm)	Dimensions (inch)	Max RPM	Box Qty
DCG1006016	100X6.0X16	4X1/4X5/8	15200	25
DCG1156022	115X6.0X22.2	4 1/2X1/4X7/8	13300	25
DCG1256022	125X6.0X22.2	5X1/4X7/8	12200	25
DCG1506022	150X6.0X22.2	6X1/4X7/8	10200	25
DCG1806022	180X6.0X22.2	7X1/4X7/8	8600	25
DCG2306022	230X6.0X22.2	9X1/4X7/8	6600	25