

Rotary Cam Switch

This rotary cam switch is designed for diverse electrical applications. It is rated for high voltage and current applications and features clearly marked terminal connections.



Overview

LW26GS Rotary Cam Switch

The LW26GS series rotary switch is engineered for reliable performance in diverse industrial and commercial electrical applications. Designed for versatility, it functions effectively as a control switch, transfer switch, or motor control switch. The series is available in two distinct configurations: a common type with a black plate and handle, and a quick-stop type featuring a yellow plate and red handle for enhanced visibility and safety.

Technical Specifications

Operational Life

8500 cycles

Non-load Operations

1500 cycles

Load Operations

10000 cycles

Total Operations

Current and Power Ratings

Ith (A)	AC-21A (A)	AC-22A (A)	AC-23A (A)	Power (kW)
20	20	20	15	7.5
25	25	25	22	11
32	32	32	30	15
63	63	63	57	30
125	100	100	90	45
160	150	150	135	75

Rated Working Voltage

440 V

Available Rated Thermal Currents

20A, 25A, 32A, 63A, 125A, 160A

Installation & Mounting

ANDELI **LW26GS**

LW26GS Series Par-lock Type Switches

1. General Information

2. Technical Specifications

Model	Current Rating (A)	Number of Poles	Mounting Plate	Handle Color	Plate Color
LW26GS1	20	1	M1	Red	Black
LW26GS2	25	1	M1	Red	Black
LW26GS3	32	1	M2	Red	Black
LW26GS4	63	1	M2	Red	Black
LW26GS5	125	1	M3	Red	Black
LW26GS6	160	1	M3	Red	Black
LW26GS7	20	2	M1	Red	Black
LW26GS8	25	2	M1	Red	Black
LW26GS9	32	2	M2	Red	Black
LW26GS10	63	2	M2	Red	Black
LW26GS11	125	2	M3	Red	Black
LW26GS12	160	2	M3	Red	Black
LW26GS13	20	3	M1	Red	Black
LW26GS14	25	3	M1	Red	Black
LW26GS15	32	3	M2	Red	Black
LW26GS16	63	3	M2	Red	Black
LW26GS17	125	3	M3	Red	Black
LW26GS18	160	3	M3	Red	Black

3. Dimensions and Installation (Dimensions in mm)

Overview of available current ratings and compatible mounting plates for the LW26GS series.

Compatible Escutcheon Plates

- M1 (20A, 25A)
- M2 (20A, 25A, 32A, 63A)
- M3 (32A, 63A, 125A, 160A)

Design Options

Available Configurations

Common Type (Black Plate/Handle) • Quick Stop Type (Yellow Plate/Red Handle)