

# S-N Series AC Contactor

The S-N Series AC Contactor is designed for electrical switching applications. It is used to control power to electrical circuits, providing reliable performance.

Specifications							
Model	Rated Heat current(A)	Rated Working current(A)			AC-3 Control power (kW)		
		220V	380V	660V	220V	380V	660V
S-N10	20	11	9	5	2.2	3.3	3.3
S-N11	20	13	12	7	3	4	4.5
S-N12	25	13	12	7	3	4	4.5
S-N20	32	22	22	9	5.5	10	10
S-N21	32	22	22	9	5.5	10	10
S-N25	50	30	30	12	8.5	14	14
S-N35	60	40	40	17	12	20	20

## Product Overview

### Industrial Contactor Efficiency

The S-N Series AC Contactor is designed to provide robust switching capabilities for demanding industrial applications. These units deliver reliable performance across a range of current capacities from 20A to 60A. Engineered for versatility, they support various AC-3 control power requirements to ensure optimal operation in diverse electrical environments.

## Technical Performance

### Model Ratings Table

Model	Rated Heat Current (A)	220V Current (A)	380V Current (A)	660V Current (A)
S-N10	20	11	9	5
S-N11	20	13	12	7
S-N12	25	13	12	7
S-N20	32	22	22	9
S-N21	32	22	22	9
S-N25	50	30	30	12
S-N35	60	40	40	17

### AC-3 Control Power by Model

Model	220V (kW)	380V (kW)	660V (kW)
S-N10	2.2	3.3	3.3
S-N11	3	4	4.5
S-N12	3	4	4.5
S-N20	5.5	10	10
S-N21	5.5	10	10
S-N25	8.5	14	14
S-N35	12	20	20