

Self-Priming Jet Pump

This self-priming jet pump is suitable for ambient temperatures up to 40°C and fluid temperatures up to 40°C. It can handle a maximum pressure of 10 bar.

Type	Power (HP)	Power (kW)	Max. Flow (l/min)	Max. Head (m)	Suction Head (m)	Rotational Speed (R.P.M)	PACKAGE DIMENSIONS (mm)			
							A	B	M	Hg
JET60B	0.5	0.37	42	38	9	2850	118	165	200	112
JET80B	0.75	0.55	48	46	9	2850	128	180	210	122
JET100B	1	0.73	54	52	9	2850	138	190	220	132

ADDITIONAL IMAGES



Product Overview

High-Performance Self-Priming Jet Pumps

The JETB series injection-type pumps combine centrifugal force with nozzle technology to provide reliable, high-head performance. Designed for clean water applications, these units excel at rapid self-priming and are perfect for domestic water supply, pressure boosting, and garden irrigation. Their robust design ensures durability, making them an ideal choice for both residential and agricultural environments.

Key Features

Capabilities

Self-Priming, High Head, Deep Suction, Clean Water Compatible, Pressure Boosting

Technical Specifications

Performance Overview

54 l/min

Maximum Flow

52 m

Maximum Head

9 m

Suction Head

2850 R.P.M

Rotational Speed

Model Comparisons

Model	Power (HP)	Q.max (l/min)	H.max (m)	Net Weight (kg)
JET60B	0.5	42	38	9
JET80B	0.75	48	46	9
JET100B	1	54	52	9

Installation Requirements

Placement Instructions

- Install in a covered area
- Protect against adverse weather conditions
- Suitable for wells and swimming pools
- Compatible with surge tanks and pressure switches