

# Single Phase DIN Rail Energy Meter

This single-phase energy meter is designed for DIN rail mounting. It accurately measures active energy (kWh) and is suitable for sub-metering applications.



## ADDITIONAL IMAGES



## Overview

### Professional Single-Phase Energy Monitoring

The DEM-3M1C is a versatile single-phase DIN rail energy meter designed for precise measurement in residential, public, and industrial environments. It features bi-directional metering, making it an ideal solution for solar energy applications where monitoring both imported and exported energy is critical. With its high-contrast backlit LCD and optional Modbus communication, it provides a reliable and easy-to-integrate solution for modern energy management systems.

## Key Performance Metrics

### Key Performance Metrics

**100 A**

Max Current

**1 s**

Accuracy Class

**230 V**

Rated Voltage

**1600 imp/kWh**

Pulse Constant

## Electrical Specifications

Rated Voltage	230 V
Current Range	10A (Base) / 100A (Maximum)
Frequency	50/60Hz
Auxiliary Power Supply	85-275V AC

## Measurement Capabilities

### Measured Parameters

- Active Energy
- Reactive Energy
- Voltage (RMS)
- Current (RMS)
- Frequency
- Max Demand
- Import/Export Energy (Bi-directional)

## Communication & Output

### Output Interfaces

- RS-485 Modbus-RTU (Optional)
- Digital Pulse Output (1600imp/kWh)

## Physical & Environmental

### Environmental Limits

Parameter	Value
Altitude	d2500m
Humidity	0~95% RH (Non-condensing)
Storage Temp	-40°C to +70°C

Mounting Type Standard 35mm DIN Rail

Operating Temperature -25°C to +55°C

## Safety & Compliance

### Insulation & Protection

- Voltage Tolerance: 2KV (1 min)
- Shock Voltage: 6KV (1.2uS waveform)
- Insulation Resistance: >5M $\Omega$

### Certifications & Standards

CE • IEC62053-21 Class 1