

Stainless Steel Banding Buckle

This stainless steel banding buckle features a dentiform locking mechanism for secure fastening. Constructed from SUS 304, it provides excellent corrosion resistance and high tensile strength.



Product Overview



High-durability SUS 304 stainless steel harness buckle designed for industrial strapping applications.

Dentiform Locked Harness Buckle

These dentiform locked harness buckles are engineered for use with stainless steel banding and strapping. Constructed from high-quality SUS 304 stainless steel, they provide superior corrosion resistance and high tensile strength suitable for demanding industrial and outdoor environments. The specialized dentiform locking mechanism ensures a consistent, secure grip that prevents slippage and maintains reliable tension over time.

Material and Performance



The dentiform locking mechanism provides a secure and reliable grip, preventing banding slippage in harsh conditions.

Material Characteristics	SUS 304 Stainless Steel, Acid-proof, Corrosion Resistant, High Tensile Strength
Finish	Uncoated

Technical Specifications

Model Specifications

Model	Width	Thickness	Packing
TSBD-8	1/4 (8mm)	0.5	100
TSBD-10	3/8 (10mm)	1	100
TSBD-12.7	1/2 (12.7mm)	1.2	100
TSBD-16	5/8 (16mm)	1.2	100
TSBD-19	3/4 (19mm)	1.2	100
TSBD-10	3/8 (10mm)	1.2	100
TSBD-12.7	1/2 (12.7mm)	1.5	100
TSBD-16	5/8 (16mm)	1.5	100
TSBD-19	3/4 (19mm)	1.5	100