

# Submersible Aquarium Pump 200L/H 1.6m

This submersible pump is designed for aquariums and small water features. It has a maximum head of 1.6 meters and a flow rate of 200 liters per hour.



## ADDITIONAL IMAGES



## Product Overview

### Versatile Submersible Solution

This compact and efficient submersible pump is engineered for reliable water circulation in both freshwater and saltwater environments. Featuring a brushless, permanent magnetic drive, it ensures long-term performance and low-noise operation. With a 200L/H flow rate and a 1.6m maximum head, it is the ideal solution for aquariums and small water feature applications.

## Technical Specifications

### Key Performance Metrics

**200 L/H**

Flow Rate

**1.6 m**

Max Head

**4.8 W**

Power Consumption

### Electrical Data

Parameter	Value
Rated Voltage	12V DC
Max Rated Current	0.4A
Noise Level	<35dB

## Operation & Durability

### Operating Conditions

- Submersible installation
- Suitable for fresh and salt water
- Max working temperature: 60 Celsius
- Dry run and blocking protection available (optional)

### Compatible Power Sources

Solar Panel • DC Electric Source • Adapter • Battery

### Durability and Materials

ABS Material, Brushless Motor, IP68 Waterproof, 30,000+ Hours Lifespan